




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H01Q 1/24, 9/30	A1	(11) International Publication Number: WO 97/42680 (43) International Publication Date: 13 November 1997 (13.11.97)
(21) International Application Number: PCT/SE97/00734 (22) International Filing Date: 30 April 1997 (30.04.97) (30) Priority Data: 9601706-6 3 May 1996 (03.05.96) SE (71) Applicant (for all designated States except US): ALLGON AB [SE/SE]; P.O. Box 500, S-184 25 Åkersberga (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): ENGBLOM, Gunnar [SE/SE]; Mönstringsvägen 160, S-184 33 Åkersberga (SE). (74) Agents: SVAHN, Stefan et al.; Axel Ehmers Patentbyrå AB, P.O. Box 10316, S-100 55 Stockholm (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: 'AN ANTENNA DEVICE HAVING A MATCHING MEANS**(57) Abstract**

An antenna device is disclosed, which is intended for a portable radio communication device, in particular a pocket size cellular telephone. The novel antenna device includes a housing (1) having mounting means (2) for mounting on the telephone (3), helically configured first radiator (4) carried by the housing, and an impedance matching means (6) formed by reactive components on a dielectric substrate provided with a printed circuit pattern. The matching means is carried by the housing and it matches an impedance of the first radiator to an impedance of transceiver circuitry of the telephone. The antenna device may include one or more radiators in addition to the first radiator. The disclosed antenna means is particularly advantageous when the antenna device includes at least one radiator of half-wave type.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CN	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

AN ANTENNA DEVICE HAVING A MATCHING MEANS

The present invention relates to an antenna device having a carrier structure and a matching means. In particular, the invention concerns an antenna device for a mobile personal telephone. More specifically, the invention is directed towards an antenna device with at least one radiating element having half-wave characteristics.

One way of making use of several advantages of the invention, is applying it to an antenna device having a fixed helical radiator in combination with an extendable and retractable straight radiator, at least one being essentially of half-wave type.

In a radio communication device the transmitting/receiving circuits are coupled to the feed point of a radiator means via a feed line. Normally, the transmitting/receiving circuits have a nominal impedance of $50 + j0$ ohms. If the impedance of the radiator feed point differs substantially from that of the transmitting/receiving circuits, an impedance matching means is required for matching the impedance of the radiator to the impedance of transmitting/receiving circuits.

The radiator and the impedance matching means may then be interconnected by a first feed line or similar having a given length. The first feed line is influenced electromagnetically by different conductive or dielectric bodies in its surroundings, for example, a support on which the radio device is resting, the hand and head of an operator, or the chassis of the radio device or conductive parts thereof. Especially when the radiator feed point impedance is high, the length of the first feed line is significant to the environmental influence on the antenna performance. The higher the impedance of the feed point and the longer the first feed line, the higher the sensitivity to environmental variations.

A radiator of quarter-wave type may not require an impedance

matching means to be connected to 50 ohm circuitry. Sometimes, a quarter-wave radiator is preferred since it allows the antenna means to be relatively short and non-obstructive. However, a drawback of quarter-wave radiators, for example in
5 cellular telephones, is that currents are inevitably generated on the chassis of the telephone. The antenna performance is then sensitive to influence by, for example, the operator holding the telephone or pressing it to his ear.

10 Also, from another point of view, it is desirable to use a radiator with relatively high impedance, for example a half-wave radiator or similar. Generally, a half-wave radiator provides a higher efficiency and a greater overall length resulting in less screening. Particularly, on a small size
15 cellular telephone, screening by the operator's head is a problem with regard to operating range and absorption of radiation in the human body.

An antenna device called RA 3137, designed by Allgon Antenn AB
20 in 1993, includes a housing carrying a straight essentially half-wave radiator, a coaxial connector, and an impedance matching means connecting the radiator and the connector. The impedance matching means consists mainly of a coil located inside a cylindrical ground portion, and interconnecting the
25 radiator feed point and the center pin of the connector. Both the coil and the connector are expensive components in manufacture and assembly. RA 3137 is considered to be the prior art closest to the invention.

30 US-A-5,300,940 discloses a similar antenna device for a mobile radio communication device. That antenna device includes a helical or straight radiator and at least one reactive element in the form of, for example, a coil on a core for adapting the radiator impedance and for obtaining a desired bandwidth.

35 The two above mentioned antenna devices fail to be cost-effective, compact, and provide ease of manufacture in large quantities.

WO 94/10720 discloses an antenna device which comprises a housing carrying a helical radiator and an extendable straight half-wave type radiator, which are connected to an impedance matching means inside a portable telephone. The contents of WO
5 94/10720 are incorporated herein by reference.

Apparently, problems related to the use of a half-wave type radiator in a mobile radio communication device (a telephone) are: the presence of a high-impedance feed line which is
10 sensitive to disturbance and the need of an impedance matching network which will excessively occupy space inside the telephone or the antenna base.

One object of the present invention is to provide an antenna device according to the introductory portion of claim 1, the
15 first element being substantially directly connected to the impedance matching means, and the impedance matching means being compact.

20 Other objects of the invention are to provide antenna devices that are suitable for production in large quantities, and that facilitate a design process thereof.

These objects are attained in an antenna device according to
25 the characterising portion of claim 1.

A further advantage of the inventive antenna device is that it enables a well-defined and standardized impedance of the interface of the telephone. This greatly facilitates telephone
30 testing in production and service when the antenna is removed, since test instruments have interfaces of standardized impedance.

The radiating element(s) of the device may be of different
35 types that require impedance transformation for connection to transceiver circuits, but radiating element(s) of half-wave type are preferred. Such antennas are essentially independent of a ground plane.

For mass production it is advantageous that the substrate is a miniature printed circuit board, or a flexible film substrate, having conductive film circuits, possibly also including reactive structures. Further, a circular or annular geometry of the substrate is preferred for ease of mounting in a base of the housing perpendicularly to a direction in which the first element extends. Several other geometries and orientations of the substrate are possible, including an elongated or square form arranged parallel to the first element (possible having some type of edge or edge-mounted connector for contacting the telephone) and even substrates having bends or angles.

The antenna device is advantageously connected to the radio device via a transmission line which is not coaxial in order to avoid complicated and expensive connectors.

In an antenna device for a small-size cellular telephone, it is preferred to have at least one helically configured radiating element. For better performance when required, the helical element may be combined with an essentially straight radiator which is extendable and retractable. The substrate may then carry a contact member for contacting the straight radiator when extended.

In particular, the invention may be advantageously applied when further radiating elements are included in the common housing for operating within a wider frequency band or within two more separated frequency bands. The impedance may need a greater number of reactive components, but it would be possible to provide separate connections to the telephone for separate frequency bands.

Embodiments of the invention will be described in detail below with references to the drawing, wherein:

Fig. 1 is a partly cross-sectional view of a first embodiment of an antenna device having a helical radiator and an impedance matching network and being mounted on a cellular telephone; Fig. 2 is a perspective view of the impedance matching network

of fig. 1 in the form of a PCB with reactive components;
Fig. 3 is a partly cross-sectional view of a second embodiment
of an antenna device, which differs from that of fig. 1 mainly
in that it further comprises an extendable and retractable
5 antenna whip having a straight radiator in a lower portion;
Fig. 4 is a perspective view of the impedance matching network
of fig. 3, which differs from that of fig. 2 mainly in that it
further comprises a contact member as a part of the network for
contacting the straight radiator when the whip is extended;
10 Fig. 5 is a partly cross-sectional view of a third embodiment
of an antenna device, which differs from that of fig. 3 mainly
in that its helical radiator begins with a substantially
straight portion and that its impedance matching means is
located at the bottom of the antenna housing which extends into
15 the telephone chassis;
Fig. 6 is a bottom view of the antenna device and the telephone
of fig. 5.

With reference to fig. 1, the antenna means of a first
20 embodiment comprises an essentially cylindrical antenna housing
1 of a flexible dielectric material which is mounted by snap-in
mounting means 2 in an essentially circular opening in a
chassis 13 of a cellular telephone 3. The housing 1 carries a
helical radiator 4 having a feed point 5 which exhibits a
25 relatively high impedance, e.g. 200 ohms, an impedance matching
means 6 formed by a miniature printed circuit board 12 in the
shape of a disc located at a lower end of the housing
perpendicular to an axis, which is common to the housing and
the helical radiator, and having surface-mounted reactive
30 components 11, a first and second connecting means 7, 8
connected to the radiator 4 and, by metal wire segments (first
and second conductive members) 9, 10, to transceiver circuits
(not shown) of the telephone 3, respectively, the circuits
exhibiting a relatively low impedance, e.g. 50 ohms.

35 The telephone 3 includes a printed circuit board 14 having
connecting means 15, 16 for receiving the metal wire segments
9, 10. The connecting means 15, 16 are conventionally used

female connectors soldered to circuit board conductors 17, 18 leading to the transceiver circuitry.

5 With reference to fig. 2 the printed circuit board 12 of the impedance matching means 6 includes a conductor segment 19 inter-connecting the first connecting means 7 and a first side of a first reactive component 11, a conductor segment 20 inter-connecting the second connecting means 8, 9, a first side of a second reactive component 11, and a second side of the first
10 reactive component 11, a conductor segment 21 inter-connecting the second connecting means 8, 10 and a second side of the second reactive component 11.

15 This integration of the impedance matching means 6 in the housing 2 requires practically no length of a transmission path having a high impedance between the feed point 5 and the reactive components 11. Thus, influences from the surroundings on such a high-impedance path are minimized. Further, a 50 ohms transmission line, or similar depending on the case, is
20 substantially obtained through the segments 9, 10, the connectors 15, 16, and the printed circuits 17, 18. Alternatively, the connectors 15, 16 on the telephone circuit board 14 may be formed by flexible metal tongues.

25 With reference to fig. 3, the antenna means of a second embodiment has all features described above in relation to the first embodiment. Moreover, the second embodiment comprises an antenna whip 22 having a non-conductive upper end portion 24 and an essentially straight radiator 23 included in its lower
30 portion. The antenna whip 22 is carried by the housing 1 so that it is extendable and retractable along a common axis of the housing 1 and the helical radiator 4. The printed circuit board 12 of the impedance matching means 6 is provided with an opening through which the antenna whip 22 is movable.

35 When the antenna whip 22 is retracted (not shown) it extends into the chassis of the telephone 3 through a non-conductive protective tube 26, which is fastened in the antenna housing 1,

and the upper end portion 24 extends inside the full height of the helical radiator 4. In the retracted position, the helical radiator 4 effects practically all the antenna function.

5 When the antenna whip 22 is extended (shown in fig. 3) it extends upwards essentially from the impedance matching means 6 through the housing 1 and the helical radiator 4. The straight radiator 23 is then connected to the impedance matching means 6 in parallel with the helical radiator 4 by means of a
10 connecting member 25 at the opening in the circuit board 12. In the extended position, the straight radiator 23 effects the essential part of the antenna function.

15 With reference to fig. 4 the printed circuit board 12 of the impedance matching means 6 of the second embodiment includes all features of the impedance matching means of the first embodiment and, in addition thereto, a conductor segment 27 inter-connecting the first connecting means 7, the first side of the first reactive component 11, and the connecting member
20 25, which makes contact with a lower end of the straight radiator 23 when the antenna whip 22 is in its extended position.

25 This integration of the impedance matching means 6 in the housing 2 gives the same advantages as those described in relation to the first embodiment. Also, the connectors 15, 16 on the telephone circuit board 14 may alternatively be formed by flexible metal tongues.

30 With reference to figs. 5 and 6, the antenna device of a third embodiment includes most features of the second embodiment as shown in figs. 3 and 4, with the main exceptions being that the mounting means 2 of the antenna housing is adapted for mounting into a rather high cylindrical opening in the telephone chassis
35 30, that the impedance matching means 6 is mounted in a slightly conical recess in the lower end of the housing and is enclosed inside the chassis 30 of the telephone (which is however non-conductive), that a lower end portion 31 of the

helical radiator leads in an essentially straight configuration from a upper end level of the chassis 30 to the impedance matching means 6 (reactive components thereof not shown), that the lower end portion 31 is provided with a flexible bend 32
5 departing from the straight configuration and forming, instead of the impedance matching means itself, a contact member for connecting to the a lower portion of the straight radiator when the latter is in its extended position, and that the printed circuit board 14 of the telephone is provided with flexible
10 metal tongues 28, 29 for connection to the antenna means.

Although the invention has been described in relation to specific embodiments, it is to be understood that many more variations are possible without departing from the scope of the
15 invention. Such variations are, for instance, to include in the impedance matching means a switching means that is operated by the extension of the slidable antenna whip, in order to allow radiating elements of different types (half and quarter wave), to arrange the substrate of the impedance matching means in
20 cylindrical or essentially flat configuration in parallel with the antenna housing and radiator axes, and to provide separated circuits in the impedance matching means for two or more conductively separated radiating elements.

25 Other variations are, for instance, to replace the helical radiator in the aforementioned embodiments with a radiator having meander configuration, as a single meander conductor, or multiple meander conductors, with common or separate feed points. Further variations are, for instance, to replace the
30 helical radiator in the aforementioned embodiments with multiple helical radiator(s).

CLAIMS

1. An antenna device for a portable radio communication device operating within UHF or adjacent frequency ranges, comprising:

- 5 - a housing (1) having mounting means (2) for mounting on a radio communication device (3),
- a radiating first element (4) carried by the housing (1),
- the first element (4) having a first feed point (5) at which it exhibits a first impedance Z_1 ,
- 10 - an impedance matching means (6) being carried by the housing (1) adjacent to the first feed point (5) and having first and second coupling means (7, 8) exhibiting essentially the first impedance Z_1 and a second impedance Z_2 , respectively,
- 15 - the first coupling means (7) being connected to the first feed point (5),
- the second coupling means (8) including first and second conductive members (9, 10) to be connected to the radio communication device,
- 20 - the impedance matching means including at least one reactive element (11) connected between the first and second electrical coupling means (7, 8),
- c h a r a c t e r i z e d b y
- the impedance matching means (6) including a dielectric
- 25 substrate (12) carried by the housing (1),
- the substrate (12) carrying the reactive element(s) (11) and a conductor pattern (19, 20, 21, 27), which interconnects the reactive element(s) (11) and the
- coupling means (7, 8).

30

2. The antenna device according to claim 1, wherein:

- the first element (4) is essentially of half-wave type.

3. The antenna device according to claim 1 or 2, wherein:

- 35 - the substrate is a printed circuit board.

4. The antenna device according to claim 1 or 2, wherein:

- the substrate is a flexible film carrier having

conductive film circuits.

5. The antenna device according to any of the preceding claims, wherein:

- 5 - the substrate has an at least partly circular outer edge for mounting in a corresponding groove or recess in a base of the housing,
- the substrate is mounted substantially perpendicular to a direction in which the first element extends.

10

6. The antenna device according to any of the preceding claims, wherein:

- the first and second conductive members (9, 10) are non-coaxially configured.

15

7. The antenna device according to any of the preceding claims, wherein:

- the first element is helically configured.

20

8. The antenna device according to any of claims 1-6, wherein:

- the first element is essentially straight.

9. The antenna device according to any of claims 1-6, wherein:

- the radiating first element is helically configured,
- 25 - a radiating second element which is an essentially straight radiator is slidable through the first element along an essentially common axis,
- the substrate has an annular form to permit the second element to be retracted through it.

30

10. The antenna device according to claim 9, wherein:

- the substrate carries a contact member for contacting the second element when extended.

35

11. The antenna device according to any of the preceding claims, comprising:

- further radiating means for operating within a wider frequency band or within two or more separated frequency

bands.

12. The antenna device according to any of the preceding claims, wherein:

- 5 - a reactive element (11) carried by the substrate (12) is connected between the first and second conductive members (9, 10).

1/2

Fig. 1





Fig. 2

Fig. 3





Fig. 4

2/2

Fig. 6





Fig. 5



INTERNATIONAL SEARCH REPORT

International application No. —

PCT/SE 97/00734

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H01Q 1/24, H01Q 9/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H01Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9507556 A1 (ALLGON AB), 16 March 1995 (16.03.95), figures 1-3, abstract --	1-12
A	EP 0718909 A2 (NOKIA MOBILE PHONES LTD.), 26 June 1996 (26.06.96), abstract --	1-12
A	US 5300940 A (KENNETH D. SIMMONS), 5 April 1994 (05.04.94), cited in the application --	1-12
A	WO 9410720 A1 (ALLGON AB), 11 May 1994 (11.05.94), cited in the application -- -----	1-12

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

- * Special categories of cited documents:
- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed
- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

28 August 1997

Date of mailing of the international search report

02. 09. 97

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Rune Bengtsson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

06/08/97

International application No.
PCT/SE 97/00734

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	9507556	A1	16/03/95	AU	7626294 A	27/03/95
				CA	2170984 A	16/03/95
				EP	0717881 A	26/06/96
				SE	500983 C	10/10/94
				SE	9302870 A	10/10/94

EP	0718909	A2	26/06/96	GB	2296603 A	03/07/96
				GB	9426229 D	00/00/00
				JP	8237013 A	13/09/96

US	5300940	A	05/04/94	NONE		

WO	9410720	A1	11/05/94	CA	2147007 A	11/05/94
				CN	1086633 A	11/05/94
				DE	667044 T	15/02/96
				EP	0667044 A,B	16/08/95
				JP	7508868 T	28/09/95
				SE	501551 C	13/03/95
				SE	9203199 A	30/04/94

THIS PAGE BLANK (USPTO)